

M12 Megapixel lenses



(4K)

(Model) :	HN--3020-4K	(Mount)	M12*P0.5-6g
(Pixles)	8MP	(Element)	8G
(F/NO)	2.0±5%	(Application)	CCTV
(EFL)	2.8mm	(FOV 1/2.3")	D:175°
(M-BFL)	4.3±0.1mm		H:135°
(TTL)	23.2±0.3mm		V:99°
(Image circle)	1/2.3 "		



(4K)

(Model) :	HN--8036-4K	(Mount)	M12*P0.5-6g
(Pixles)	8MP	(Element)	8G
(F/NO)	2±5%	(Application)	CCTV
(EFL)	3.6mm	(FOV 1/2.5")	D:120°
(M-BFL)	5.2±0.1mm		H:84°
(TTL)	23.0±0.3mm		V:52°
(Image circle)	1/2.5"		



(4K)

(Model) :	HN-8060-4K	(Mount)	M12*P0.5-6g
(Pixles)	8MP	(Element)	8G
(F/NO)	2±5%	(Application)	CCTV
(EFL)	6±5%mm	(FOV 1/2.5")	D:70°
(M-BFL)	5.2±0.1mm		H:50°
(TTL)	23.0±0.3mm		V:32°
(Image circle)	1/2.5 "		Will Launch soon....



(Star-light)

(Model) :	HN-SL2029	(Mount)	M12*P0.5-6g
(Pixles)	2MP/4MP/6MP	(Element)	4G4P
(F/NO)	1.4±5%	(Application)	CCTV
(EFL)	2.8±5%mm	(FOV 1/2.3")	D:135°
(M-BFL)	5.2±0.1mm		H:114°
(TTL)	23.5±0.3mm		V:62°
(Image circle)	1/2.7 "		Will Launch soon....



(Star-light)

(Model) :	HN-SL3039	(Mount)	M12*P0.5-6g
(Pixles)	2MP/4MP/6MP	(Element)	3G3P
(F/NO)	1.4±5%	(Application)	CCTV
(EFL)	4.0±5%mm	(FOV 1/2.5")	D:111°
(M-BFL)	5.6±0.1mm		H:97°
(TTL)	23.5±0.3mm		V:54°
(Image circle)	1/2.7 "		

M12 Megapixel lenses



(Star-light)

(Model) :	HN-SL2027	(Mount)	M12*P0.5-6g
(Pixles)	2MP/4MP/6MP	(Element)	3G3P
(F/NO)	1.4±5%	(Application)	CCTV
(EFL)	6.0±5%mm	(FOV 1/2.3")	D:64°
(M-BFL)	5.2±0.1mm		H:57°
(TTL)	23.5±0.3mm		V:31.5°
(Image circle)	1/2.7 "	Will Launch soon....	



(6MP)

(Model) :	HN-PB60501	(Mount)	M12*P0.5
(Pixles)	3MP/6MP	(Element)	
(F/NO)	2.5±5%	(Application)	CCTV
(EFL)	5.0mm±5%	(FOV 1/1.8")	D:105°
(M-BFL)	7.64±0.1mm		H:84°
(TTL)	32.85±0.1mm		V:52°
(Image circle)	Φ9.2(1/1.8")	2MP \$0.99; 6MP \$1.35	



(2MP)

(Model) :	HN-3018	(Mount)	M12*P0.5
(Pixles)	2MP	(Element)	5G
(F/NO)	2.2±5%	(Application)	CCTV, Automotive,
(EFL)	1.8mm±5%	(FOV 1/2.3")	D:155°
(M-BFL)	3.1±0.1mm		H:120°
(TTL)	17.7±0.3mm		V:89°
(Image circle)	Φ4.5(1/4")	2MP \$1.35	



(2MP/4MP)

(Model) :	HN--2028	(Mount)	M12*P0.5
(Pixles)	2MP、4MP	(Element)	2G3P
(F/NO)	2.0±5%	(Application)	CCTV
(EFL)	2.8mm	(FOV 1/2.5")	D:135°
(M-BFL)	5.7±0.1mm		H:117°
(TTL)	22.7±0.3mm		V:63°
(Image circle)	Φ6.6(1/2.7 ")	2MP \$1.6; 4MP \$1.85	



(2MP/4MP)

(Model) :	HN--3036	(Mount)	M12*P0.5
(Pixles)	2MP、4MP	(Element)	2G2P
(F/NO)	2.0±5%	(Application)	CCTV, Automotive
(EFL)	4.0mm±5%	(FOV 1/2.5")	D:120°
(M-BFL)	5.3±0.1mm		H:88°
(TTL)	22.5±0.3mm		V:64°
(Image circle)	Φ6.7(1/2.5")	2MP \$0.99; 4MP \$1.35	

M12 Megapixel lenses



(2MP/4MP)

(Model) :	HN--2026A1	(Mount)	M12*P0.5
(Pixles)	2MP、4MP	(Element)	2G2P
(F/NO)	2.0±5%	(Application)	CCTV, Automotive
(EFL)	6.0mm±5%	(FOV 1/2.5")	D:69.5°
(M-BFL)	5.2±0.1mm		H:55°
(TTL)	22.5±0.3mm		V:41°
(Image circle)	Φ7.2(1/2.5 ")		



(4MP6MP)

(Model) :	HN-8003	(Mount)	M12*P0.5
(Pixles)	4MP、6MP	(Element)	7G
(F/NO)	2.0±5%	(Application)	CCTV
(EFL)	12±5%mm	(FOV 1/2.3")	D:34°
(M-BFL)	5.7±0.1mm		H:28°
(TTL)	21.8±0.3mm		V:20°
(Image circle)	Φ7.2(1/2.5")		



(3MP)

(Model) :	SBV2812ICR-3M	(Mount)	M12 / D14
(Pixles)	3MP	(Element)	7G
(F/NO)	1.8±5%	(Application)	CCTV
(EFL)	2.8-12±5%mm	(FOV 1/2.3")	D:136°
(M-BFL)	13.5±0.1mm		H:109°
(TTL)	50.6±0.3mm		V:81.6°
(Image circle)	1/2.7"	ICR , IR, DC Iris	



(3MP)

(Model) :	SBV2812ICR-3M	(Mount)	M12 / D14
(Pixles)	3MP	(Element)	7G
(F/NO)	1.8±5%	(Application)	CCTV
(EFL)	2.8-12±5%mm	(FOV 1/2.3")	D:136°
(M-BFL)	13.5±0.1mm		H:109°
(TTL)	50.6±0.3mm		V:81.6°
(Image circle)	1/2.7"	ICR , IR, Manual Iris	